



Part Number 75-110-14 V-Rod Muscle Competition Series Slip-Ons Exhaust System (09-10)

Congratulations, you have purchased the finest exhaust system available for your motorcycle. Your Vance & Hines exhaust is designed and crafted for maximum performance, a great sound and unbeatable style. Please follow the instructions below, check exhaust system for missing or damaged parts and if you need any assistance please contact our technical support line (562) 921-7461.

ATTENTION:

This exhaust system is for racing purposes only.

STOCK EXHAUST SYSTEM REMOVAL

Please remove the following:

1. To remove the stock mufflers loosen and remove the two nuts holding the muffler to the passenger foot-peg. Remove foot-peg assembly and set aside. Loosen and remove the single nut towards rear of the muffler which holds the muffler to the round bar section of the foot-peg/exhaust bracket. Loosen muffler clamp and pull muffler away from head pipe to set aside. Repeat for both sides.

COMPETITION SERIES EXHAUST SYSTEM INSTALLATION

1. Install supplied muffler clamps onto head pipes and leave loose.
2. Slide Mufflers onto stock head pipes being sure that the brackets go onto the footpeg studs and rear bracket studs.
3. Reinstall foot-pegs and tighten the three mounting nuts on each side.
4. Tighten muffler clamps, torque to 75 in.lbs.
5. Clean all fingerprints from the exhaust using a contact cleaner (or other non flammable cleaner). Fingerprints will leave stains on the pipe once the motorcycle is started.
6. You are now ready to start the motorcycle.

Note: After initial ride it is recommended to re-torque the baffle screw to 8-10 lb. using a 5/32" allen wrench.

For best results, we recommend fuel injection mapping for your new combination using a Fuelpak or Power Commander. Settings for the Fuelpak and some Power Commander maps are available on our website at www.vanceandhines.com

Vance & Hines

13861 Rosecrans Ave, Santa Fe Springs, CA 90670

Phone: (562) 921-7461, Fax: (562) 802-0110

E-mail: sales@vanceandhines.com

Web: www.vanceandhines.com

Opening Hours – Monday through Friday, 8am – 5pm, Pacific Standard Time

Vance & Hines exhaust systems are warranted against defects in material and workmanship for a period of 90 days from the date of purchase from an authorized dealer. This warranty does not cover discoloration of any coated finishes. This warranty is limited to the repair or replacement of a product proven to be defective from normal use. Vance & Hines exhaust systems are designed to fit and operate on OEM motor and chassis. This warranty does not cover any product subject to abuse, misuse, improper installation or modification.

75-110-14: V-ROD MUSCLE COMPETITION SERIES SLIP-ONS
PNC EXHAUST SYSTEM

| 75-110-14 PARTS LIST | | |
|----------------------|------------------------------|------|
| PART NO. | DESCRIPTION | QTY. |
| D271RP | Muscle Muffler Assy. Lt | 1 |
| D270RP | Muscle Muffler Assy. Lt | 1 |
| A210NP | Name Plate, Rt (2.5") | 1 |
| A211NP | Name Plate, Lt (2.5") | 1 |
| A506HW | Rivet | 4 |
| A334HW | System Clamp, Ø1 7/8" | 2 |
| A120BEC | Muscle Slip-Ons EndCap Rt. | 1 |
| A125BEC | Muscle Slip-Ons EndCap Lt. | 1 |
| A122R | Baffle Core Assy. | 2 |
| A444HW | 18-8 SS Capscrew 10-32, 3/8" | 6 |
| A445HW | BHCS 1/4"-20 x 5/8", Zinc | 2 |
| A235HW | BHCS 1/4"-20 x 1/2", Zinc | 2 |
| A112HW | Flat Washer Zinc, 1/4" | 4 |
| A115HW | Lock Washer Zinc, 1/4" | 4 |
| A261FG | Baffle Sock | 2 |

DRAG SPECIALTIES PART#: 1801-0343

STOCK EXHAUST: 25.6 lbs
75-104-10 EXHAUST: 14 lbs

